Tighten the lug nuts a few turns in a star pattern.

## **How to Change a Flat Tire**

1. Watch the "How To Change Your Tire Alone" video on the Mountain Home Driver Education Facebook page or go to this link: <a href="https://www.youtube.com/watch?v=AT">https://www.youtube.com/watch?v=AT</a> pPIJTiyE 2. Place the following steps in the correct order by writing the numbers 1-13 in the blank beside the step. (NOTE: there are some decoy/dangerously incorrect steps mixed in the list!) Completely remove the lug nuts. Turn the jack clockwise to raise the car. Park the car on a hill and shift the transmission into Neutral. Do NOT set the parking brake! Remove the flat tire. \_\_\_\_\_ Completely tighten all lug nuts in a star pattern before removing the jack. Install the spare tire with the valve stem should be facing out. Park on level ground, set the parking brake, and shift the transmission into Park. Manual transmission vehicles should be shifted into 1st gear or Reverse. Partially loosen the lug nuts ½ turn using a star pattern. \_\_\_\_ Jump up and down on the front or rear bumper to see if the car will stay on the jack. Jack up the car high enough to remove the flat tire and install the spare tire. \_\_\_\_ Lower the jack by turning the handle counterclockwise so that the tire is touching the ground. \_\_\_\_ Take off the hub cap (if necessary). \_\_\_\_ Crawl under the car to see if the jack is securely attached to the frame of the car. Put a heavy object such as a brick in front of the tire diagonally opposite of the flat tire (although the video does not mention this, it is a good idea to put an object on both sides of the tire). Put the jack under the frame of the car near the wheel with the flat tire.